


DESCRIPTION

The ST2301D is the P-Channel logic enhancement mode power field effect transistor is produced using high cell density, DMOS trench technology.

This high density process is especially tailored to minimize on-state resistance.


These devices are particularly suited for low voltage application such as cellular phone and notebook computer power management and other batter powered circuits, and low in-line power loss are needed in a very small outline surface mount package.

**PIN CONFIGURATION
SOT-23**



1.Gate 2.Source 3.Drain

FEATURE

- -20V/-2.0A, $R_{DS(ON)} = 180\text{m-ohm (Typ.)}$
@ $V_{GS} = -4.5\text{V}$
- -20V/-1.5A, $R_{DS(ON)} = 360\text{m-ohm}$
@ $V_{GS} = -2.5\text{V}$
- Super high density cell design for extremely low $R_{DS(ON)}$
- Exceptional on-resistance and maximum DC current capability
- SOT-23 package design

**PART MARKING
SOT-23**


D; Product Code A: Process Code



ORDERING INFORMATION

Part Number	Package	Part Marking
ST2301DSRG	SOT-23	01DA

※ Process Code : A ~ Z ; a ~ z

※ ST2301DSRG S : SOT-23 ; R : Tape Reel ; G : Pb – Free



ST2301D 

P Channel Enhancement Mode MOSFET

-2.0A







ABSOLUTE MAXIMUM RATINGS (Ta = 25°C Unless otherwise noted)

Parameter	Symbol	Typical	Unit
Drain-Source Voltage	V _{DSS}	-20	V
Gate-Source Voltage	V _{GSS}	±12	V
Continuous Drain Current (T _J =150°C)	I _D	T _A =25°C -2.0	A
		T _A =70°C -1.2	
Pulsed Drain Current	I _{DM}	-6.0	A
Continuous Source Current (Diode Conduction)	I _S	-1.6	A
Power Dissipation	P _D	T _A =25°C 1.25	W
		T _A =70°C 0.8	
Operation Junction Temperature	T _J	150	°C
Storage Temperature Range	T _{STG}	-55/150	°C
Thermal Resistance-Junction to Ambient	R _{θJA}	105	°C/W






ELECTRICAL CHARACTERISTICS (Ta = 25°C Unless otherwise noted)


Parameter	Symbol	Condition	Min	Typ	Max	Unit
Static						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=-250\mu A$	-20			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=-250\mu A$	-0.3		-1.0	V
Gate Leakage Current	I_{GSS}	$V_{DS}=0V, V_{GS}=\pm 12V$			± 100	nA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=-20V, V_{GS}=0V$			-1	uA
		$V_{DS}=-20V, V_{GS}=0V$ $T_J=55^\circ C$			-5	
On-State Drain Current	$I_{D(on)}$	$V_{DS}\leq -4.5V, V_{GS}=-5V$	-2.0			A
Drain-source On-Resistance	$R_{DS(on)}$	$V_{GS}=-4.5V, I_D=-2.0A$		0.180		Ω
		$V_{GS}=-2.5V, I_D=-1.5A$		0.360		
Forward Transconductance	g_{fs}	$V_{DS}=-5V, I_D=-2.8V$		0.5		S
Diode Forward Voltage	V_{SD}	$I_s=-1.6A, V_{GS}=0V$		-0.8	-1.2	V
Dynamic						
Total Gate Charge	Q_g	$V_{DS}=-10V$ $V_{GS}=-4.5V$ $I_D=-0.7A$		1.5	2.0	nC
Gate-Source Charge	Q_{gs}			0.3		
Gate-Drain Charge	Q_{gd}			0.35		
Turn-On Time	$t_{d(on)}$ t_r	$V_{DD}=-10V$ $R_L=10\Omega$ $I_D=-1.0A$ $V_{GEN}=-4.5V$ $R_G=6\Omega$		5	10	nS
				15	25	
Turn-Off Time	$t_{d(off)}$ t_f			8	15	
				1.4	1.8	

TYPICAL CHARACTERISTICS (25°C Unless noted)



TYPICAL CHARACTERISTICS (25°C Unless noted)



SOT-23 PACKAGE OUTLINE


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.100	0.035	0.043
A1	0.000	0.100	0.000	0.004
A2	0.900	1.000	0.035	0.039
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.550REF		0.022REF	
L1	0.300	0.500	0.012	0.020
theta	0°	8°	0°	8°