


DESCRIPTION

ST9435A is the P-Channel logic enhancement mode power field effect transistor which is produced using high cell density, DMOS trench technology. This high density process is especially tailored to minimize on-state resistance. These devices are particularly suited for low voltage application such as battery pack, notebook computer power management, and other battery powered circuits.

PIN CONFIGURATION SOP-8




FEATURE

- -30V/-5.6A, $R_{DS(ON)} = 57m\Omega$ (Typ.) @ $V_{GS} = -10V$
- -30V/-5.0A, $R_{DS(ON)} = 72m\Omega$ @ $V_{GS} = -6.0V$
- -30V/-4.4A, $R_{DS(ON)} = 95m\Omega$ @ $V_{GS} = -4.5V$
- Super high density cell design for extremely low $R_{DS(ON)}$
- Exceptional on-resistance and maximum DC current capability
- SOP-8 package design

PART MARKING SOP-8



S : Subcontractor Y : Year Code
A : Process Code



P-Channel

ORDERING INFORMATION

Part Number	Package	Part Marking
ST9435AS8RG	SOP-8P	ST9435A
ST9435AS8TG	SOP-8P	ST9435A

※ Process Code : A ~ Z ; a ~ z

※ ST9435AS8RG S8 : SOP-8 ; R : Tape Reel ; G : Pb – Free

※ ST9435AS8TG S8 : SOP-8 ; T : Tube ; G : Pb – Free

**ST9435A**

P Channel Enhancement Mode MOSFET

- 5.6A**ABSOLUTE MAXIMUM RATINGS** (Ta = 25°C Unless otherwise noted)

Parameter		Symbol	Typical	Unit
Drain-Source Voltage		VDSS	-30	V
Gate-Source Voltage		VGSS	±20	V
Continuous Drain Current (TJ=150°C)	TA=25°C TA=70°C	ID	-6.5 -4.6	A
Pulsed Drain Current		IDM	-30	A
Continuous Source Current (Diode Conduction)		IS	-2.3	A
Power Dissipation	TA=25°C TA=70°C	PD	2.5 1.6	W
Operation Junction Temperature		TJ	150	°C
Storage Temperature Range		TSTG	-55/150	°C
Thermal Resistance-Junction to Ambient		RθJA	70	°C/W






ST9435A






P Channel Enhancement Mode MOSFET

- 5.6A


ELECTRICAL CHARACTERISTICS (Ta = 25°C Unless otherwise noted)





Parameter	Symbol	Condition	Min	Typ	Max	Unit
Static						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=-250\mu A$	-30			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=-250\mu A$	-1.0		-3.0	V
Gate Leakage Current	I_{GSS}	$V_{DS}=0V, V_{GS}=\pm 20V$			± 100	nA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=-24V, V_{GS}=0V$			-1	uA
		$V_{DS}=-24V, V_{GS}=0V$ $T_J=85^{\circ}C$			-5	
On-State Drain Current	$I_{D(on)}$	$V_{DS}=-5V, V_{GS}=-4.5V$	-10			A
Drain-source On-Resistance	$R_{DS(on)}$	$V_{GS}=-10V, I_D=-5.6A$ $V_{GS}=-6.0V, I_D=-5.0A$ $V_{GS}=-4.5V, I_D=-4.4A$		0.057 0.072 0.095		Ω
Forward Transconductance	g_{fs}	$V_{DS}=-15V, I_D=-5.7V$		13		S
Diode Forward Voltage	V_{SD}	$I_S=-2.3A, V_{GS}=0V$		-0.8	-1.2	V
Dynamic						
Total Gate Charge	Q_g	$V_{DS}=-15V, V_{GS}=-10V$ $I_D=-3.5A$		16	24	nC
Gate-Source Charge	Q_{gs}			2.3		
Gate-Drain Charge	Q_{gd}			4.5		
Input Capacitance	C_{iss}	$V_{DS}=-15V, V_{GS}=0V$ $f=1MHz$		680		pF
Output Capacitance	C_{oss}			120		
Reverse Transfer Capacitance	C_{rss}			75		
Turn-On Time	$t_{d(on)}$ t_r	$V_{DD}=-15V, R_L=15\Omega$ $I_D=-1A, V_{GEN}=-10V$ $R_G=6\Omega$		14	25	nS
Turn-Off Time	$t_{d(off)}$ t_f			16	26	
				43	70	
				30	52	

TYPICAL CHARACTERISTICS


TYPICAL CHARACTERISTICS


TYPICAL CHARACTERISTICS



PACKAGE OUTLINE SOP-8P


SYMBOLS	DIMENSIONS IN MILLIMETERS			DIMENSIONS IN INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	1.47	1.60	1.73	0.058	0.063	0.068
A1	0.10	—	0.25	0.004	—	0.010
A2	—	1.45	—	—	0.057	—
b	0.33	0.41	0.51	0.013	0.016	0.020
C	0.19	0.20	0.25	0.0075	0.008	0.0098
D	4.80	4.85	4.95	0.189	0.191	0.195
E	5.80	6.00	6.20	0.228	0.236	0.244
E1	3.80	3.90	4.00	0.150	0.154	0.157
e	—	1.27	—	—	0.050	—
L	0.38	0.71	1.27	0.015	0.028	0.050
 y	—	—	0.076	—	—	0.003
Ø	0°	—	8°	0°	—	8°